

DEB56

6" LED EYEBALL DOWNLIGHT



The perfect LED downlight for wall lighting and sloped ceilings, The DEB56 provides the flexibility for those applications where the standard DLR56 doesn't quite fit. With 360 degrees of rotation and 35 degrees of adjustable tilt in both directions the DEB56 gives you the ability to aim over 900 lumens exactly where it's needed.

FEATURES

- Durable stamped steel construction with die cast aluminum heat sink
- Polycarbonate diffuser and reflector cone create a uniform light distribution that reduces glare
- Greater than 90 CRI and an R9 greater than 50
- Dimmable to 10% with most standard dimmers
- Thermally protected, high efficiency driver standard
- Operating temperature rating of 0°F to 120°F (-18°C – 49°C)
- LM-79, LM-80 testing performed in accordance with IESNA standards
- Quick and easy installation with a screw-in Edison base (GU24 socket string available) and torsion spring mounting system

PRODUCT SPECIFICATIONS

Series	Input Voltage (VAC)	Delivered Lumens (Lm)	System Level Power (W)	System Efficacy (Lm/W)	Color Rendering Index (CRI)
DEB56-20-120-3K-WH	120	971	13	75	91

ORDERING INFORMATION

Example: DEB56-20-120-3K-WH

Series	Version	Voltage	CCT's	Trim Color
DEB56	20 (2.0)	120	2K (2700) 3K (3000) 4K (4000)	WH (white)

